

Specifications 6 Series Push-Pull

Travel	Bulkhead End		Clamp End		Operating Loads	
Inch/mm	DIM "A" Inch/(mm)	DIM "B" Inch/(mm)	DIM "C" Inch/(mm)	DIM "D" Inch/(mm)	Push Lbs./(N)	Pull Lbs./(N)
1.0 (25.4)	3.25 (82.6)	5.00 (127.0)	2.56 (65.0)	4.31 (109.5)	250 (1112)	400 (1779)
2.0 (50.8)	4.25 (108.0)	6.50 (165.1)	3.56 (90.4)	5.81 (147.6)	250 (1112)	400 (1779)
3.0 (76.2)	5.25 (133.4)	8.00 (203.2)	4.56 (115.8)	7.31 (185.7)	210 (934)	400 (1779)
4.0 (101.6)	6.25 (158.8)	9.50 (241.3)	5.56 (141.2)	8.81 (233.8)	170 (756)	400 (1779)
5.0 (127.0)	7.25 (184.2)	11.00 (279.4)	6.56 (166.6)	10.31 (261.9)	130 (578)	400 (1779)
6.0 (152.4)	8.25 (209.6)	12.50 (317.50)	7.56 (192.0)	11.81 (299.9)	90 (400.5)	400 (1779)
7.0 (177.8)	9.25 (235)	14.00 (355.6)	8.56 (217.4)	13.31 (338.0)	60 (267)	400 (1779)